

13. (Amended) A comminuted cellulosic fibrous material treatment system, comprising:

- a digester having a comminuted cellulose material inlet at the top thereof;
- a first vessel, at a first pressure, containing comminuted cellulosic fibrous material, and having a top, a bottom, and an outlet adjacent said bottom;
- a conduit having an inlet directly connected to and communicating with the outlet of said first vessel, and an outlet;
- a second vessel, having a width dimension greater than said conduit, for receiving the cellulosic material from said conduit and having a level of liquid therein; and
- a slurry pump having an inlet for receiving material from the second vessel and an outlet operatively connected to the inlet of said digester.

18. (Amended) A comminuted cellulosic fibrous material treatment system comprising:

- a digester having a comminuted cellulose material inlet at the top thereof;
 - a first vessel, at a first pressure, containing comminuted cellulosic fibrous material, and having a top, a bottom, and an outlet adjacent said bottom;
 - a conduit having an inlet communicating with the outlet of said first vessel, and an outlet;
 - a second vessel, having a width dimension greater than said conduit, for receiving the cellulosic material from said conduit and having a level of liquid therein; and
 - a slurry pump having an inlet for receiving material from the second vessel and an outlet operatively connected to the inlet of said digester, wherein
- said second vessel comprises a tank having a substantially right cylinder upper portion; and a substantially right circular cone frustum lower

2
portion, said tank and said conduit being substantially concentric
and in liquid communication with each other, and
wherein said slurry pump is operatively connected to said conduit by a
connecting conduit or transition; and wherein there is a gap
between said conduit and said connecting conduit or transition; and
wherein said tank substantially surrounds said gap.

21. (Amended) A comminuted cellulosic fibrous material treatment system
comprising:

3
a digester having a comminuted cellulose material inlet at the top thereof;
a first vessel, at a first pressure, containing comminuted cellulosic fibrous
material, and having a top, a bottom, and an outlet adjacent said
bottom;
a conduit having an inlet communicating with the outlet of said first vessel,
and an outlet;
a second vessel, having a width dimension greater than said conduit, for
receiving the cellulosic material from said conduit and having a
level of liquid therein; and
a slurry pump having an inlet for receiving material from the second vessel
and an outlet operatively connected to the inlet of said digester,
wherein
said second vessel comprises a tank, and wherein said slurry pump is
operatively connected to said conduit by a connecting conduit or
transition; and wherein there is a gap between said conduit and
said connecting conduit or transition; and wherein said tank
substantially surrounds said gap.

23. (Amended) A comminuted cellulosic fibrous material treatment system
comprising:

4
a digester having a comminuted cellulose material inlet at the top thereof;